



<b>APT20-5S</b>	
<b>5MP 7"Outdoor High Speed PTZ IR 120m</b>	
<b>Video Output Mode</b>	<b>H.265/ H.264 Compression Method</b>
<b>Image Sensor</b>	1/2.8"SONY Starvis Back-illuminated CMOS sensor
<b>Image Resolution</b>	5MP
<b>Compression</b>	H.265/H.264
<b>Minimum Illumination</b>	0.01Lux
<b>S/N Ratio</b>	>50db
<b>Scanning System</b>	Progressive Scan
<b>Video Output</b>	Network
<b>PTZ</b>	
<b>Horizontal Rotation Speed</b>	120°/S
<b>Horizontal Rotation Range</b>	0°~360°
<b>Tilt Rotation Speed</b>	30°/s
<b>Tilt Rotation Range</b>	0°~93°
<b>Preset Points</b>	220
<b>Guard Tours</b>	3 groups
<b>Guard Points</b>	Max.16 points
<b>Lens</b>	
<b>Focus Length</b>	4.7mm-94mm
<b>Focus Control</b>	20X Optical Zoom
<b>Lens</b>	
<b>Infrared LED</b>	Φ 42x6PCS IR LEDS + 2PCS Laser LED
<b>IR Range</b>	120m
<b>Day-night mode</b>	AUTO
<b>Network</b>	
<b>Ethernet</b>	RJ-45 (10/100Base-T)
<b>Protocol</b>	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP,P2P
<b>ONVIF</b>	Support ONVIF 2.4
<b>P2P</b>	YES, Support QR Code
<b>POE</b>	Support IEEE 802.3af
<b>Stream type</b>	Main Stream / Sub Stream / MJPEG
<b>General</b>	
<b>Weatherproof</b>	IP66
<b>Operating Temperature</b>	Indoor: 0°~ +40° Outdoor: -40°~ +60°
<b>Operating Humidity</b>	≤90% Non Condensing
<b>Power</b>	DC12V/4A
<b>Lightning Protection</b>	31x31x44(cm)
<b>Weight</b>	10.7Kgs