



ASCS150-SW

5MP Outdoor Full Time Color Dome up to 25m

Video Output Mode	H.265+/H.265/H.264+/H.264 Compression Method
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Image Resolution	5MP
Effective Pixels	2616 (H) x 1964 (V))
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI
TV System	PAL/NTSC
Electronic Shutter	Auto: PAL 1/25-1/10000Sec; NTSC 1/30-1/10000Sec
Minimum Illumination	0.01Lux
S/N Ratio	≥52dB
Scanning System	Progressive Scan
Video Output	Network
Lens	
Focus Length	2.8 mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	5MP
Night Vision	
Light LED	Support Warm light LED 4000K
Light Distance	Up to 25M
led Status	Auto Control
led Power On	Smart, Manual & Timed mode
Network	
Ethernet	RJ-45 (10/100Base-T)
Wireless	NO
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS, DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Support IEEE 802.3af
Main Stream	2592*1944@20fp / 2592*1536@30fp
Sub Stream	720*480@30fps
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Defog Mode	Support
BLC	Support
WDR	HDR: 120dB
OSD Support	YES
General	
Housing	Metal, IP67
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 1000mA
Dimension	∅ 96 x 91(H) mm