



<b>ASEC2150-Q</b>	
<b>5MP Outdoor Fixed Dome IP IR 20m</b>	
<b>Video Output Mode</b>	<b>H.265+/H.265/H.264+/H.264 Compression Method</b>
<b>Image Sensor</b>	1/2.7" SmartSens CMOS sensor
<b>Image Resolution</b>	5MP
<b>Effective Pixels</b>	2888(H)*1628(V)
<b>Compression</b>	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
<b>TV System</b>	PAL/NTSC
<b>Electronic Shutter</b>	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
<b>Minimum Illumination</b>	0.01Lux
<b>S/N Ratio</b>	≥52dB
<b>Scanning System</b>	Progressive Scan
<b>Video Output</b>	Network
<b>Smart Analytics</b>	Human/ Face Detection, Intrusion detection
<b>Lens</b>	
<b>Focus Length</b>	2.8mm
<b>Focus Control</b>	Fixed
<b>Lens Type</b>	Fixed
<b>Pixels</b>	4MP
<b>Night Vision</b>	
<b>Infrared LED</b>	14μ x 18PCS
<b>Infrared Distance</b>	20M
<b>IR Status</b>	Auto Control
<b>IR Power On</b>	Smart, Manual & Timed mode
<b>Network</b>	
<b>Ethernet</b>	RJ-45 (10/100Base-T)
<b>Wireless</b>	NO
<b>Protocol</b>	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS, DDNS,RTP,RTSP,RTCP,NTP,SMTP
<b>ONVIF</b>	Support ONVIF 2.4
<b>P2P</b>	YES, Support QR Code
<b>POE</b>	Optional, Support IEEE 802.3af
<b>Main Stream</b>	2880*1620@30fps/ 2592*1536@30fps
<b>Sub Stream</b>	720*480@15fps
<b>Camera Features</b>	
<b>Day/Night</b>	Color/ B&W (IR-CUT )
<b>Image Config</b>	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
<b>Defog Mode</b>	Support
<b>BLC</b>	Support
<b>WDR</b>	HDR: 120dB
<b>OSD Support</b>	YES
<b>General</b>	
<b>Housing</b>	Metal, IP66
<b>IR Cut Filter</b>	YES
<b>Operation Temperature</b>	-10°C ~ +50°C RH95% Max
<b>Storage Temperature</b>	-20°C ~ +60°C RH95% Max
<b>Power Source</b>	DC12V±10%, 750mA
<b>Dimension</b>	φ93 x 74(H) mm